

Running Capacitors

This product is of good electrical characteristics, self concrescence, less spoilage. It is applied to the AC, DC and pulsate circuit of Electromotor, Water pump, Air Compressor, Air Conditioner, etc.



Barrel type wire running 450v capacitors

| TYPE | MFD |
|------|------|
| BRW | 1.5 |
| BRW | 2 |
| BRW | 2.25 |
| BRW | 2.5 |
| BRW | 3 |
| BRW | 3.5 |
| BRW | 4 |
| BRW | 5 |
| BRW | 6 |
| BRW | 7 |
| BRW | 8 |
| BRW | 10 |
| BRW | 12 |
| BRW | 13 |
| BRW | 14 |
| BRW | 15 |
| BRW | 16 |
| BRW | 18 |
| BRW | 20 |
| BRW | 25 |
| BRW | 30 |
| BRW | 35 |
| BRW | 40 |
| BRW | 45 |
| BRW | 50 |
| BRW | 55 |
| BRW | 60 |
| BRW | 70 |
| BRW | 80 |
| BRW | 90 |



Barrel type pins running 450v capacitors

| TYPE | MFD |
|------|------|
| BRP | 5 |
| BRP | 6 |
| BRP | 7 |
| BRP | 8 |
| BRP | 10 |
| BRP | 12 |
| BRP | 12.5 |
| BRP | 13 |
| BRP | 14 |
| BRP | 16 |
| BRP | 18 |
| BRP | 20 |
| BRP | 25 |
| BRP | 30 |
| BRP | 35 |
| BRP | 40 |
| BRP | 45 |
| BRP | 50 |
| BRP | 55 |
| BRP | 60 |

Barrel 450v nut & wiers capacitors

| TYPE | MFD |
|------|-----|
| BNW | 16 |
| BNW | 20 |
| BNW | 25 |



Barrel 450v nut & pins capacitors

| TYPE | MFD |
|------|------|
| BNP | 12.5 |
| BNP | 16 |
| BNP | 20 |
| BNP | 25 |
| BNP | 30 |
| BNP | 35 |



Box type wire running 450v capacitors

| TYPE | MFD |
|------|------|
| XW | 1 |
| XW | 1.2 |
| XW | 1.5 |
| XW | 1.8 |
| XW | 2 |
| XW | 2.25 |
| XW | 2.5 |
| XW | 3 |
| XW | 3.5 |
| XW | 4 |
| XW | 4.5 |
| XW | 5 |
| XW | 6 |



Box type pin running 450v capacitors

| TYPE | MFD |
|------|-----|
| XP | 1.5 |
| XP | 2 |
| XP | 2.5 |
| XP | 4 |
| XP | 6 |
| XP | 8 |
| XP | 10 |
| XP | 12 |
| XP | 16 |
| XP | 20 |
| XP | 24 |

Running & Starting Capacitors



There are advantages of low dissipation factors, high insulation resistance, good self healing character, steady function, resisting flowing current and high carrier capability, anti-explosive device and safety reliability, suitable for compressors or air conditioners and beneficial to the starting and running of motors.



Starting capacitors 230/250v with brackets

| TYPE | MFD |
|------|-----------|
| SP | 100 |
| SP | 150 |
| SP | 200 |
| SP | 250 |
| SP | 300 |
| SP | 350 |
| SP | 400 |
| SP | 50-63 |
| SP | 60-80 |
| SP | 80-110 |
| SP | 100 - 125 |
| SP | 125 - 175 |
| SP | 175 - 225 |
| SP | 200 - 250 |
| SP | 250 - 275 |
| SP | 300 - 375 |
| SP | 400 - 475 |
| SP | 500 - 575 |



Barrel 450v oil capacitors air conditioners

| TYPE | MFD |
|------|---------|
| AP | 2.5 (s) |
| AP | 2.5 |
| AP | 16 |
| AP | 20 |
| AP | 25 |
| AP | 30 |
| AP | 35 |
| AP | 40 |
| AP | 45 |
| AP | 50 |
| AP | 55 |
| AP | 60 |
| AP | 100 |



Starting capacitors 230/250v blue color

| TYPE | MFD |
|------|-----|
| SWB | 100 |
| SWB | 150 |
| SWB | 200 |
| SWB | 250 |
| SWB | 300 |
| SWB | 350 |
| SWB | 400 |
| SWB | 500 |
| SWB | 600 |